



STEP
INDUSTRIAL
FILTERS

HMU40

Caudal: 40l/min

Carcasa: HMM050130-1

TENSIÓN DE 380 VAC/50Hz

AC/50Hz BELLTA (U)

MADE IN SPAIN

STEP
INDUSTRIAL
FILTERS

Element

Model

HMI0050300-1

MADE IN U.K.

STEP
INDUSTRIAL
FILTERS

Filtration mobile units

Step Industrial Filters filtration mobiles units guarantee optimum filtration for hydraulic oil or fuel tanks, with a wide range of micron ratings, adjusting to every need of filtration.



HMU20

PUMP: vanes

ELECTRIC MOTOR: 1,2 kw 230 v single-phase feeding

FLUID: hydraulic oil

RECOMMENDED VISCOSITY: ISO VG 32/46/68

FLUID RECOMMENDED TEMPERATURE: 20°C a 65°C

INLET/OUTLET CONEXION: 3/4" / 3/4"

INLET/OUTLET HOSE LENGTH: 3 meters/ 3 meters

HMU40

PUMP: gears

ELECTRIC MOTOR: 0,75 kW 230v / 400v 50Hz three-phase feeding

FLUID: hydraulic oil

RECOMMENDED VISCOSITY : ISO VG 32/46/68

FLUID RECOMMENDED TEMPERATURE: 20°C a 65°C

INLET/OUTLET CONEXION: 3/4" / 3/4"

INLET/OUTLET HOSE LENGTH: 3 meters/ 3 meters





FMU18

FILTER: Separ SWK2000/18

NOMINAL FLOW: 18 l/min

TRANSFER CARRIAGE: Tuthill PA1 – 60 a 220V

MICRONAGE OPTIONS: 10 μ , 30 μ

FLUID: diesel fuel

BSP CONEXION: 3/4"

Special filtration needs:

HMU2/MIC

FILTER: RMF housings and filter elements

NOMINAL FLOW: 2,1 l/min

ENGINE: single-phase feeding 1CV

MICRONAGE OPTIONS: 0,5 μ , 1 μ , 3 μ , 6 μ , 12 μ

MICRFILTRATION: removal of water and solid particles

BSP CONEXION: 1/2"





STEP INDUSTRIAL FILTERS
HMU20

Caudal: 20
Carcasa: HH
TENSIÓN DE MANIO



STEP INDUSTRIAL FILTERS
Industry Department
Telf.: (+34) 916 707 212
industria@filtroscartes.com
www.filtroscartes.com

